

**AMERICAN
TECHNOLOGY**



FOUR WHEELER / AUTOMOTIVE BATTERIES

MORE POWER TO YOU

**SMF & MF
BATTERIES**

**Ca-Ca
Silver+**



Conditions Apply*



MAINTENANCE FREE



HIGH POWER



SELENIUM INSIDE

FOUR WHEELER AUTOMOTIVE BATTERIES

SPECIFICATION CHART

	X POWER RANGE				XX POWER RANGE							
Container Type as per NEW JIS	Model Name	Warranty (In Months)	CCA Ambient	Reserve Capacity (RC) min.	Model Name	Warranty (In Months)	CCA Ambient	Reserve Capacity (RC) min.	Capacity At C20	Dimensions in{mm}		
										L	W	H

JIS RANGE (PASSENGER CAR)

36B20R	TPX36B20R	24*	200	34					32	197	129	227
36B20L	TPX36B20L	24*	200	34					32	197	129	227
44B20R	TPX44B20R	50*	400	54	TPXX44B20R	72*	460	55	35	197	129	227
44B20L	TPX44B20L	50*	400	54	TPXX44B20L	72*	460	55	35	197	129	227
44B20L (BH)	TPX44B20L(BH)	50*	400	54	TPXX44B20L(BH)	72*	460	55	35	197	129	227
55B24L	TPX55B24L	50*	460	73	TPXX55B24L	72*	550	80	45	238	129	227
85D23L	TPX85D23L(BH)	50*	620	114	TPXX85D23L(BH)	72*	640	118	68	259	173	225
65D26R	TPX65D26R	50*	550	85	TPXX65D26R	72*	500	112	60	259	173	225
65D26L	TPX65D26L	50*	550	85	TPXX65D26L	72*	500	112	60	259	173	225
80D26R (BH)	TPX80D26R	50*	630	115	TPXX80D26R	72*	600	120	65	259	173	225
80D26L (BH)	TPX80D26L	50*	630	115	TPXX80D26L	72*	600	120	65	259	173	225
105B20L	TPX105D31R	50*	430	135					80	306	173	225

DIN RANGE (PASSENGER CAR)

DIN44(54434)	TPXDIN44L	50*	420	56	TPXXDIN44L	72*	420	73	44	207	175	190
DIN50(55054 L)	TPXDIN50L	50*	525	73	TPXXDIN50L	72*	430	75	50	207	175	190
DIN55(55548R)	TPXDIN55R	50*	510	73	TPXXDIN55R	72*	480	91	55	242	175	190
DIN55(55530 L)	TPXDIN55L	50*	510	73	TPXXDIN55L	72*	480	91	55	242	175	190
DIN60(56030)	TPXDIN60L	50*	620	90	TPXXDIN60L	72*	540	108	60	242	175	190
DIN66 (56628)	TPXDIN66L	50*	640	91	TPXXDIN66L	72*	580	109	66	278	175	190
DIN74 (57412)	TPXDIN74L	50*	650	110	TPXXDIN74L	72*	670	128	74	278	175	190
DIN80 (58043)	TPXDIN80L	50*	860	128	TPXXDIN80L	72*	740	147	80	315	175	190
DIN100 (60030)	TPXDIN100L	50*	950	166	TPXXDIN100L	72*	850	185	100	353	175	190

PRODUCT FEATURES

- High cranking performance
- Optimized grid structure
- Durable and robust design
- Suitable for Indian weather tropical climates
- Using best grade pure lead, PP containers, lid, seperator and chemicals
- Calcium -Calcium -tin and calcium -silver maintenance-free battery
- Robust design and high vibration resistance to perform in all ground conditions
- Factory-charged batteries in ready-to-use condition
- Double chamber container with condensation mechanism
- Expanded metal grid technology
- Low self discharge

Conditions Applied*

Channel Partner/Dealer



www.teslapowerusa.in
support@teslapowerusa.com

APAC Office:
#1003-4-5, Tower-1,
DLF Corporate Greens,
Sector 74A, Gurugram,
Haryana-122004 (INDIA)

Corporate Office:
Suite #635 S 4000,
Hollywood Blvd Hollywood,
Florida, USA- 33021

Registered Office:
358/3524, Silverside Road,
Wilmington, Delaware,
U.S.A. -19810-4929