

AMERICAN
TECHNOLOGY



INVERTER TUBULAR BATTERIES

MORE POWER TO YOU



LOW MAINTENANCE



HIGH POWER



SELENIUM INSIDE



Conditions Apply*

INVERTER TUBULAR BATTERIES

SPECIFICATION CHART

Model Number	Range	Capacity @ At C20 Rate	Warranty (In Months)	Dimensions in{mm}			Charging Current (Amps)
				L	W	H	
TALL TUBULAR XX POWER RANGE							
TP1600TTXX	IT	160	90*	405	192	490	16
TP1800TTXX	IT	180	90*	405	192	490	18
TP2100TTXX	IT	210	90*	405	192	490	21
TP2400TTXX	IT	240	90*	405	192	490	24
TALL TUBULAR X POWER RANGE							
TP1600TTX	IT	160	78*	405	192	490	16
TP1800TTX	IT	180	78*	405	192	490	18
TP2100TTX	IT	210	78*	405	192	490	21
TP2400TTX	IT	240	78*	405	192	490	24
JUMBO TUBULAR XX POWER RANGE							
TP1350JTXX	JUMBO	135	54*	525	267	260	13.5
TP1500JTXX	JUMBO	150	54*	525	267	260	15

Conditions Apply*

PRODUCT FEATURES

- Using best grade PP containers and lid
- Tubular positive plate made with PDC Machine of ZIBO
- High tensile resistance / Porosity polyester gauntlets
- High Porosity PE Envelope separators from DARAMIC, USA
- Micro porous ceramic vent plug
- Heavy duty terminals
- SS fasteners
- Double side pasting negative plate



Channel Partner/Dealer



www.teslapowerusa.in
support@teslapowerusa.com

APAC Office:
#1003-4-5, Tower-1,
DLF Corporate Greens,
Sector 74A, Gurugram,
Haryana-122004 (INDIA)

Corporate Office:
Suite #635 S 4000,
Hollywood Blvd Hollywood,
Florida, USA- 33021

Registered Office:
358/3524, Silverside Road,
Wilmington, Delaware,
U.S.A. -19810-4929